

EVX-S24

COMPACT, DISCREET,
LIGHTWEIGHT

PORTABLE DIGITAL RADIO

Give your team members a compact, discreet, and lightweight radio that allows them to be comfortable in any situation.

Worn on a belt, tucked away in a pocket or clipped to a lapel, the water-submersible and dust-proof EVX-S24 is designed to survive demanding conditions. It operates in both analogue and digital modes, so it's ideal for use with mixed fleets. And in digital mode, enjoy noise cancellation for crisp audio and clear conversations.



GOODBYE
CROSSTALK



BROADEN
YOUR REACH



COME IN LOUD
AND CLEAR



KEEP YOUR
TEAM SAFE



POWER THROUGH
THE SHIFT

GENERAL FEATURES

- Water Submersible and Dust Proof (IP67)
- Channel Capacity:
 - 256 Channels/ 16 Groups
- 4 Programmable Buttons
- 8 Character Alphanumeric Display
- Safety Features:
 - Lone Worker Alert
 - Emergency Alert
- Multiple Scan Options
- Better Radio Call Quality with AMBE+2™ Vocoder
- Battery Status Indicator (Low Battery Alert)
- Battery Saver
- Busy Channel Lock Out (BCLO)
- Time Out Timer
- Keypad Lock
- AF Minimum Volume
- Auto Power Off
- Escalating Alerts
- Low Power
- Whisper Mode
- RSSI Indicator
- Internal VOX (VH-190 Required)

SIGNALLING FEATURES

- MDC-1200® ANI Encode
 - MDC-1200 ANI
 - MDC-1200 Call Alert
 - MDC-1200 Selcall
 - MDC-1200 Radio Check
 - MDC-1200 Stun/Revive
- FleetSync® ANI Encode
- CTCSS/DCS Encode and Decode
- 2-Tone Encode/Decode
- 5-Tone Encode/Decode
- Stun/Kill/Revive (5-Tone and DTMF Pager)
- DTMF Encode/Decode
- DTMF ANI
- DTMF Paging
- DTMF Speed Dial

ANALOGUE MODE FEATURES

- Busy Tone Lock Out (BTLO)
- Auto Range Transponding System (ARTS™)
- Voice Inversion Encryption

DIGITAL MODE FEATURES

- Direct Mode
- Transmit Interrupt
- Site Search
- Message Control and Privacy
- Text Message
- All, Group and Private Call
- Basic and Enhanced Privacy
- Radio Check
- Radio STUN/REVIVE
- Remote Monitor (Decode)
- Call Alert
- Call History
- Simplex Only and Repeater Capable Encryption
- Emergency
- Radio Enable/Disable
- Scan Options:
 - Scan (Mixed Mode - Analogue/Digital Channels)
 - Scan (Operator Selectable On/Off)



GENERAL SPECIFICATIONS

| | |
|---|---|
| Frequency Range | UHF: 403 – 480 MHz |
| Dimension (H x W x D) | 91 x 55 x 31 mm (3.58 x 2.17 x 1.24 in) |
| Weight Approx. with Antenna, Belt Clip | 215 g (7.6 oz) with (PMNN4468, ATU-20, Belt Clip) |
| Display | 8 Character Alphanumeric |
| Channel Spacing | 12.5 kHz (Digital) 12.5/20/25 kHz (Analogue) |
| Number of Channels and Groups | 256/16 |
| Programmable Buttons | 4 (Front: 3, Side: 1) |
| Battery Life [5-5-90 Duty with Battery Saver] | Digital 3W: 12 Hours/Analogue 2W: 11 Hours |
| IP Rating | IP67 |
| Power Supply Voltage | 3.7 VDC (Nominal) |
| Operating Temperature Range | -30° C to +60° C (-22° F to +140° F) |
| Frequency Stability | ± 1.5 ppm |
| RF Input-Output Impedance | SMA 50 Ohm |

RECEIVER SPECIFICATIONS

measured by EN 300 086, EN 300 113

| | |
|------------------------------|---|
| Sensitivity | Analogue 20 dB SINAD: 0.4µV Digital 1% BER: 0.28µV |
| Adjacent Channel Selectivity | 70/60 dB (25 kHz/12.5 kHz) |
| Intermodulation | 65 dB |
| Spurious Rejection | 70 dB |
| Audio Output | 500 mW @ 4 Ohms 10 % THD |
| FM Hum and Noise | 45/40 dB (25 kHz/12.5 kHz) |
| Conducted Spurious Emission | -57 dBm |

TRANSMITTER SPECIFICATIONS

measured by EN 300 086, EN 300 113

| | |
|-----------------------------|--|
| Output Power | Digital 3 W/2 W/1 W/0.5 W, Analogue 2 W/1 W/0.5 W |
| Modulation Limiting | ± 5 kHz (25 kHz), ± 4 kHz (20 kHz), ± 2.5 kHz (12.5 kHz) |
| Conducted Spurious Emission | -36 dBm (≤1 GHz), -30 dBm (>1 GHz) |
| FM Hum and Noise | 45/40 dB (25 kHz/12.5 kHz) |
| Audio Distortion | < 5 % @ 1 kHz |
| Adjacent Channel Power | 70/60 dB |
| Analogue FM Modulation | 16K0F3E (25 kHz), 14K0F3E (20 kHz), 11K0F3E (12.5 kHz) |
| 4FSK Digital Modulation | 12.5 kHz Data: 7K60F1D/7K60FXD 12.5 kHz Voice: 7K60F1E/7K60FXE Combination of 12.5 kHz Voice and Data: 7K60F1W |
| Digital Vocoder Type | AMBE+2 |
| Digital Protocol | ETSI102 361-1, -2, -3 |

APPLICABLE MIL-STD

| Standard | Methods/Procedures | | | | |
|-------------------|--------------------|-------------------------------------|-------------------------------------|------------------------------------|--|
| | MIL 810C | MIL 810D | MIL 810E | MIL 810F | MIL 810G |
| Low Pressure | 500.1 proc 1 | 500.2 proc 2 | 500.3 proc 2 | 500.4 proc 1/2 | 500.5 proc 1/2 |
| High Temperature | 501.1 proc 1/2 | 501.2 proc 1/A1 proc 2/A1 | 501.3 proc 1/A1 proc 2/A1 | 501.4 proc 1/HOT proc 2/HOT | 501.5 proc 1/A1 proc 2/A2 |
| Low Temperature | 502.1 proc 1 | 502.2 proc 1/Cat 3 proc 2/Cat 1 | 502.3 proc 1/Cat 3 proc 2/Cat 1 | 502.4 proc 1/Cat 3 proc 2/Cat 1 | 502.5 proc 1/Cat 3 proc 2/Cat 1 proc 3/Cat 1 |
| Temperature Shock | 503.1 proc 1 | 503.2 proc 1/A1 Cat 3 | 503.3 proc 1/A1 Cat 3 | 503.4 proc 1 | 503.5 proc 1/C |
| Solar Radiation | 505.1 proc 2 | 505.2 proc 1 | 505.3 proc 1 | 505.4 proc 1 | 505.5 proc 1/A1 |
| Rain | 506.1 proc 1/2 | 506.2 proc 1/2 | 506.3 proc 1/2 | 506.4 proc 1/3 | 506.5 proc 1/3 |
| Humidity | 507.1 proc 2 | 507.2 proc 2 | 507.3 proc 2 | 507.4 | 507.5 proc 2/Agg |
| Salt Spray/Fog | 509.1 proc 1 | 509.2 proc 1 | 509.3 proc 1 | 509.4 | 509.5 |
| Dust | 510.1 proc 1 | 510.2 proc 1 | 510.3 proc 1 | 510.4 proc 1 | 510.5 proc 1 |
| Blowing Sand | – | 510.2 proc 2 | 510.3 proc 2 | 510.4 proc 2 | 510.5 proc 2 |
| Vibration | 514.2 proc 8/F, W | 514.3 proc 1/Cat 10 proc 2/Cat 3 | 514.4 proc 1/Cat 10 proc 2/Cat 3 | 514.5 proc 1/Cat 24 | 514.6 proc 1/Cat 24 |
| Shock | 516.2 proc 1/2/3/5 | 516.3 proc 1/4/6 | 516.4 proc 1/4/6 | 516.5 proc 1/4/6 | 516.6 proc 1/4/6 |

ACCESSORIES

Antennas

- ATU-6A: 400-430 MHz 165 mm (6.5")
- ATU-6B: 420-450 MHz 155 mm (6.1")
- ATU-6C: 440-470 MHz 155 mm (6.1")
- ATU-6D: 450-485 MHz 152 mm (6")
- ATU-20AS: Stubby 400-430 MHz 80 mm (3.15")
- ATU-20CS: Stubby 420-450 MHz 80 mm (3.15")
- ATU-20DS: Stubby 440-470 MHz 80 mm (3.15")
- ATU-20FS: Stubby 450-480 MHz 80 mm (3.15")
- ATU-21AS: Super Stubby 400-420 MHz 50.8 mm (2")
- ATU-21CS: Super Stubby 420-440 MHz 50.8 mm (2")
- ATU-21DS: Super Stubby 440-460 MHz 50.8 mm (2")
- ATU-21FS: Super Stubby 460-480 MHz 50.8 mm (2")

Battery

- PMNN4468: 2300 mAh Li-Ion Battery

Carry Solutions

- LCC-S24: Leather Case, Belt Loop
- LCC-S24S: Leather Case, Swivel Belt Loop
- Clip-27: Belt Clip

Chargers

- PS000042A12 Micro USB AC Charger (EU)
- PS000042A13 Micro USB AC Charger (UK)
- CD-65: Standard Single Unit Charging Cradle
- CD-66: Enhanced Single Unit Charging Cradle
- VAC-6066: Multi Unit Charger

Audio Accessories

- MH-89A4B: Earpiece Microphone
- MH-90A4B: Compact Speaker Microphone
- MH-66F4B: IP57 Submersible Speaker Microphone
- VH-190: VOX Lightweight Headset, Behind-the-Head



EVX-S24 Yellow

EVX-S24 Black



Motorola Solutions Ltd. Nova South, 160 Victoria Street, London, SW1E 5LB, UK. www.motorolasolutions.com

Availability is subject to individual country law and regulations. All specifications shown are typical unless otherwise stated and are subject to change without notice.

MOTOROLA, MOTO, MOTOROLA SOLUTIONS and the Stylized M Logo are trademarks or registered trademarks of Motorola Trademark Holdings, LLC and are used under license. All other trademarks are the property of their respective owners. © 2017 Motorola Solutions, Inc. All rights reserved. 11-2017